

APPROVED HONDA PUMPS

Minimum Specs:

Min Flow – 450 L/min

Max Weight – 60 Lbs

***Can be with or without cage**



PUMP MODEL	WB20*	WH20*	WMP20*
Pump type	Centrifugal, Self-priming	High Pressure, Centrifugal, Self-priming	Multi-purpose, Centrifugal, Self-priming
Volute	Rigid Mounted Cast Iron	Rigid Mounted Cast Iron	Rigid Mounted Fiberglass reinforced polyester
Impeller	4 Vane Cast Iron	Cast Iron	Fiberglass reinforced polyester
Mechanical Seal (Pump case / impeller)	Silicon Carbide/Silicon Carbide	Carbon/Ceramic	Carbon/Ceramic
Priming time	110 sec @ 16.4 ft.	80 sec. at 16.4 ft.	65 sec. at 16.4 ft.
Discharge capacity	164 gal/min, 620 L/min	119 gals./min, 450 L/min	220 gals./min, 832 L/min
Suction/Discharge port diameter	2" NPT	2" NPT	2" NPT
Maximum pressure	45 psi	64 psi	44 psi
L x W x H	19.3" x 14.4" x 16.5"	20.5" x 15.7" x 18.1"	20.5" x 15.7" x 17.7"
Dry weight	44 lb.	60 lb.	57 lbs.
Fuel Capacity/Run Time at Max Discharge	2 L / 1.7 Hr.	3.1 L / 1.5 Hr.	3.1 L / 1.5 Hr.
Warranty	3 years	3 years	3 years
MSRP*	\$549*	\$799*	\$659*